Technical Report Documentation Page

1. REPORT No. 2. GOVERNMENT ACCESSION No.

3. RECIPIENT'S CATALOG No.

FHWA/CA/TL-90/08

4. TITLE AND SUBTITLE

The Toxicities of Selected Bridge Painting Materials and Guidelines for Bridge Painting Projects

September 1990

6. PERFORMING ORGANIZATION

7. AUTHOR(S)

Harold Hunt, Jeffrey Gidley

8. PERFORMING ORGANIZATION REPORT No.

604200

9. PERFORMING ORGANIZATION NAME AND ADDRESS

Division of New Technology, Materials and Research, California DOT Sacramento, California 95807 10. WORK UNIT No.

5. REPORT DATE

11. CONTRACT OR GRANT No.

E81TL11

13. TYPE OF REPORT & PERIOD COVERED

Final

12. SPONSORING AGENCY NAME AND ADDRESS

California Department of Transportation Sacramento, California 95807

14. SPONSORING AGENCY CODE

15. SUPPLEMENTARY NOTES

This project was performed in cooperation with the U.S. Department of Transportation, Federal Highway Administration, under the research project titled, "Effects of Bridge Repainting Operations on the Environment"

16. ABSTRACT

The effects of bridge painting operations on aquatic ecosystems were studied. Bioassays using Daphnia magna, Physa gyrina, Selenastrum capricornutum, fathead minnows, and rainbow trout were performed. The results indicate that both lead pigmented and paints pigmented with zinc compounds can cause toxicity. Biocides and cleaning detergent tested were highly toxic. A set of guidelines was developed to assist highway workers in determining and mitigating the impacts of bridge painting projects on the aquatic environment. The aquatic environment is broadly defined to include all beneficial uses of water and the habitat created by the water. In the guidelines, the aquatic setting is first determined, then the nature of the project, the Area of Potential Environmental Impact and the impacts of the project are determined. Finally, mitigation is discussed.

17. KEYWORDS

Environmental Impacts, Bridge Painting, Bridge Paint, Aquatic Environment, Toxicity, Aquatic Ecosystems, Blasting Abrasive, Toxic Waste

18. No. OF PAGES: 19. DRI WEBSITE LINK

22 http://www.dot.ca.gov/hq/research/researchreports/1989-1996/90-08.pdf

20. FILE NAME

90-08.pdf

This page was created to provide searchable keywords and abstract text for older scanned research reports. November 2005, Division of Research and Innovation

State of California Department of Transportation Division of New Technology, Materials and Research

THE TOXICITIES OF SELECTED **BRIDGE PAINTING MATERIALS** AND GUIDELINES FOR **BRIDGE PAINTING PROJECTS**

Study Supervised by	Mas Hatano, P.E., Chief Office of Research, Corrosion, Enviro-Chemical & Graphics
Principal Investigator	. Bennett John, P.E.
Co-Investigators	. Jeffrey L. Gidley Harold G. Hunt
Report Prepared by	Harold G. Hunt Jeffrey L. Gidley

S. Bennett P. John, P. E.

Senior Materials & Research Engineer

Water Quality & Solid Waste

Research & Development

EARL SHIRLEY, Chief Division of New Technology,

Materials and Research

		THE THE PART OF A PART OF
I REPORT NO.	2. GOVERNMENT ACCESSION NO.	3. RECIPIENT'S CATALOG NO
FHWA/CA/TL-90/08	·	
The Toxicities of Select Materials and Guidelines Projects	5. REPORT DATE September 1990 6. Performing organization code	
7. AUTHORISI		S. PERFORMING ORGANIZATION REPORT NO.
Harold Hunt, Jeffrey Gid	lley	604200
9. PERFORMING ORGANIZATION NAME AND	18. WORK UNIT NO	
Division of New Technolo		
Materials and Research,	11. CONTRACT OR GRANT NO.	
Sacramento, California	95807	E81TT.11
12. SPONSORING AGENCY NAME AND ADDRE	13. TYPE OF REPORT & PERIOD COVERED	
California Department of	Final	
Sacramento, California	14. SPONSORING AGENCY CODE	

15. SUPPLEMENTARY NOTES

This project was performed in cooperation with the U. S. Department of Transportation, Federal Highway Administration, under the research project titled, "Effects of Bridge Repainting Operations on the Environment

16. ABSTRACT

The effects of bridge painting operations on aquatic ecosystems were studied. Bioassays using Daphnia magna, Physa gyrina, Selenastrum capricornutum, fathead minnows, and rainbow trout were performed. The results indicate that both lead pigmented and paints pigmented with zinc compounds can cause toxicity. Biocides and cleaning detergent tested were highly toxic. A set of guidelines was developed to assist highway workers in determining and mitigating the impacts of bridge painting projects on the environment. The aquatic environment is broadly defined to include all beneficial uses of water and the habitat created by the water. In the guidelines, the aquatic setting is determined, then the nature first of the project established. From the aquatic setting and nature of the project, the Area of Potential Environmental Impact and the impacts of the project are determined. Finally, mitigation is discussed.

Environmental Impacts, B Painting, Bridge Paint, Environment, Toxicity, A Ecosystems, Blasting Abr Toxic Waste	Aquatic quatic	No restrictions. This document is available through the National Technical Information Service Springfield, VA 22161		
19 SECURITY CLASSIF. (OF THIS REPORT)	20 SECURITY CLASSI	F (OF THIS PAGE)	21 NO. OF PAGES	22. PRICE
Unclassified	Unclassifie	đ		

DS-TL-1242 (Rev.6/76)

CONVERSION FACTORS

English to Metric System (SI) of Measurement

Quality	English Unit	<u>Multiply By</u>	To Get Metric Equivalent
Length	inches (in) or (")	25.40 .02540	millimetres (mm) metres (m)
	feet (ft) or (')	.3048	metres (m)
	miles (mi)	1.609	kilometres (km)
Area	square inches (in ²) square feet (ft ²) acres	6.432 × 10 ⁻⁴ .09290 .4047	square metres (m^2) square metres (m^2) hectares (ha)
Volume	gallons (gal) cubic feet (ft ³) cubic yards (yd ³)	3.785 .02832 .7646	litre (1) cubic metres (m³) cubic metres (m³)
Volume/Time (Flow)	cubic feet per second (ft ³ /s)	28.317	litres per second (1/s)
	gallons per minute (gal/min)	.06309	litres per second (1/s)
Mass	pounds (1b)	.4536	kilograms (kg)
Velocity	miles per hour (mph) feet per second (fps)	.4470 .3048	metres per second (m/s) metres per second (m/s)
Acceleration	feet per second squared (ft/s²)	.3048	metres per second squared (m/s²)
	acceleration due to force of gravity (G)	9.807	metres per second squared (m/s²)
Density	(lb/ft ³)	16.02	kilograms per cubic metre (kg/m³)
Force	pounds (lb) kips (1000 lb)	4.448 4448	newtons (N) newtons (N)
Thermal Energy	British thermal unit (Btu)	1055	joules (J)
Mechanical Energy	foot-pounds (ft-lb) foot-kips (ft-k)	1.356 1356	joules (J) joules (J)
Bending Moment or Torque	inch-pounds (in-lb) foot-pounds (ft-lb)	.1130 1.356	newton-metres (Nm) newton-metres (Nm)
Pressure	pounds per square inch (psi)	6895	pascals (Pa)
	pounds per square foot (psf)	47.88	pascals (Pa)
Plane Angle	degrees (°)	0.0175	radians (rad)
Temperature	degrees fahrenheit (°F)	$\frac{\text{°F} - 32}{1.8} = \text{°C}$	degrees celsius (°C)
Concentration	parts per million (ppm)	1	milligrams per kilogram (mg/kg)

```
A CONTRACTOR
```

indigeri Stra

NOTICE

The contents of this report reflect the views of the Division of New Technology, Materials and Research which is responsible for the facts and the accuracy of the data presented herein. The contents do not necessarily reflect the official views or policies of the State of California or the Federal Highway Administration. This report does not constitute a standard, specification, or regulation.

Neither the State of California nor the United States Government endorse products or manufacturers. Trade or manufacturers' names appear herein only because they are considered essential to the object of this document.

TABLE OF CONTENTS

			: -	Page			
EXE		E SUM		•			
1	OVE	RVIEW		1			
2.		OBJECTIVES					
3.	CON	CLUSIC	ONS AND RECOMMENDATIONS	2			
4.			TATION				
5.	BEN	EFITS.		4			
6.	BAC	KGROU	IND	5			
7.	MAT	ERIALS	S AND METHODS	8			
	7.1	Bioassa	ny Materials and Methods	8			
		7.1.1	Introduction to Bioassays	8			
	٠	7.1.2	Algae Bioassays	9			
		7.1.3	Chironomid Bioassays	10			
		7.1.4	Snail Bioassays	11			
		7.1.5	Daphnia Bioassays	12			
	•	7.1.6	Fish Bioassays	14			
		7.1.7	Water	14			
	7.2	Califor	rnia Waste Extraction Test Materials	14			
	7.3	Source	s of the Bridge Painting Materials Tested	14			
	7.4		d Work Done by the Office of	15			
	7.5	Materi	als Tested in the Bioassays	15			
8.	RES	ULTS		16			
	8.1	Result	s of the Literature Survey	16			
	8.2	Labora	atory Results	17			

	8.3		Summary of the Environmental Impacts	17
		of Brid	ge Painting	
9.	DISC	CUSSION	V	. 30
	9.1	Discuss	sion of Laboratory Results	30
•	9.2	Standar	d Special Provisions for Bridge	35
			g Projects	
		9.2.1	Standard Special Provisions for a	. 35
			Nonlead-Based Paint Over Water	
		9.2.2	Standard Special Provisions for	35
	9.3	Enviror	nmental Evaluation of New Products	. 36
	9.4	Though	nts on Future Research	37
10.	GUI	DELINE	s	. 38
	Sect	ion A-Aq	uatic Setting	. ,38
		~ .		
		Step 1.		
			aquatic habitats that are within 1 kilometer of the project	. ,38
		Step 2.	Determine the beneficial uses of	
,			water in the affected system within 1	
			kilometer upstream or downstream of the	
			project	40
	Sect	ion B. Na	ature of the Product	10

	Step 1.	Determine the number of square
٠.		feet of structure that will be cleaned
		and painted
·	Step 2.	Determine the amount and toxicity of
	Step 2.	•
٠		detergent to be used to clean the bridge
•	Step 3.	Determine the amount and toxicity of
		blasting abrasive to be used to clean
		the bridge
	Step 4.	Determine the type of paint that is on
	otop 1.	
	•	the structure that will be painted
. *	Step 5.	Determine the weight of the paint per
		square foot
	Step 6.	Determine the weight of the paint
•	Stop o.	
		material to be removed from the structure
	Step 7.	Determine the toxicity of the paint to
	,	be removed
SECTIO	N.C. DE	TERMINE THE AREA OF POTENTIAL
bleite		
	EN	VIRONMENTAL IMPACT (APEI)
	Step 1.	Bring forward from SECTION A Step 1
		the type or types of aquatic habitats that
		exist within 1 kilometer upstream or down-
		stream of the project44
	Step 2.	Bring forward from CECTION A Co O
	otop 2.	Bring forward from SECTION A Step 2 the beneficial uses of the water within 1
		kilometer mile upstream or downstream of
		the project

	Step	3.	Use the following key to determine the
			APEI of the project
	Step	4.	If there is any beneficial use of the water within
			1 kilometer of the project site, consider the
			sites of those uses to be within the APEI
SECTION	D.	DETI	ERMINE THE IMPACTS TO
		AQU.	ATIC ECOSYSTEMS
	Step	1.	Determine if the bridge painting
			waste to be produced is hazardous waste
	Step	2.	Determine the Effects of Blasting Abrasives 50
	Step	3.	Determine the Effects of Detergents or
			Other Cleaning Agents on the Aquatic
			Ecosystem
•	Step	4.	Determine the Effects of Paints and
			Coating Materials on the Aquatic
			Ecosystem
	Step	5.	Determine the Combined Toxicant Impacts
	Step	6.	Determine Any Additional Impacts
SECTION	E.	SELE	ECT MITIGATION ACTIONS FOR THE PROJECT 59
	Step	1.	Mitigating for Hazardous Waste
	Step	2.	Mitigating for Blasting Abrasive
			Toxicity
	Step	3.	Mitigating for Increased Sedimentation

	Step 4.	Mitigating for Detergent or Cleaning
		Material Toxicity
	Step 5.	Mitigating for Paint Toxicity
	Step 6.	Mitigating the Formation of Scum on
		the Surface of the Water
	Step 7.	Mitigating the Combined Toxicant Impacts
	Step 8.	Mitigating any Additional Impacts
11.	LITERATURE	
	11.1 Literature	Cited
		on Paint Formulations
12.	GLOSSARY	
13.	APPENDIXES	
	Appendix I	Tests Data
	Appendix II	Computer Programs
	Appendix III	Paint Formulations

LIST OF TABLES

	Page
Table 8.3.1	Physa gyrina Bioassay Results
Table 8.3.2	Acute Daphnia magna Bioassay Results
Table 8.3.3	Chronic Daphnia magna Bioassay Results20
Table 8.3.4	Selenastrum capricornutum Bioassay Results
Table 8.3.5	Rainbow Trout Bioassay and Fathead Minnow Bioassays
Table 8.3.6	California Waste Extraction Test Results
Table 8.3.7	San Joaquin River Bridge #29-50 California
Table 8.3.8	San Joaquin River Bridge #29-50 EP Toxicity
Table 8.3.9	Mad River Bridge 04-25R California Waste
Table 8.3.10	Mad River Bridge 04-25R EP Toxicity Test
Table 8.3.11	Russian River Bridge #10-82 California
Table 8.3.12	Russian River Bridge #10-82 EP Toxicity

EXECUTIVE SUMMARY

Introduction

The Water Quality and Solid Waste Branch of the California Department of Transportation's Division of New Technology, Materials and Research conducted research on the impacts to the

aquatic environment of bridge painting materials. The study consisted of a literature survey of

the subject and a bioassay study of materials used in bridge painting.

The objectives were to:

1 Determine the environmental impacts for existing paint systems and evaluate impacts of

paint systems proposed for use.

2. Evaluate existing paint/abrasive system residue for disposal suitability.

3. Evaluate existing cleaning materials and abrasives for aquatic impact and develop a testing

procedure to evaluate future materials.

4. Develop a method of analysis and reporting which addresses potential environmental

impacts of a painting operation and which can serve as input for the environmental

document.

5. Determine the toxicity of zinc spatter from an experimental cathodic protection system.

The materials tested were:

Black Beauty

Green Diamond

Starblast

EZ Blast

Kleen Blast

Lapis Luster and Clemco

PWB 80 paint

PWB 81 paint

PWB 83 paint

S-1

PB 197 paint

Basic lead silicochromate paint

Red lead/ aluminum paint

Vinyl paint

Blast sand contaminated with red lead /aluminum

Husky Clean Machine Formula #1

Dowicil 75

Skane M-8

Zinc spatter from an experimental cathodic protection system. This material is not to be confused with zinc-rich paints.

The formulations of the paints tested are found in Appendix III. New paint formulations were artificially aged in the laboratory. It is realized that the artificially aged paints may not have the same toxicity characteristics as paint in the field on a bridge.

Conclusions and Recommendations

The following conclusions are based on the literature search and the laboratory analysis. These conclusions should be carefully applied to individual projects.

1. At some concentration, all of the paints tested caused toxic effects in one or more of the five species tested.

When toxic amounts of paint will be generated, shrouding or other precautions should be used to prevent toxic concentrations of paint material from occurring in the aquatic environment.

The import of this conclusion should not be overly expanded. It does not mean that any paint system should be rejected for use because of this report. It means that all of the systems tested had a concentration above which toxic effects may be expected to occur. Nearly every substance has a concentration above which toxic effects may be expected to occur.

2. Both lead and zinc contaminated blasting abrasive wastes are likely to contain enough lead or zinc, respectively, to be classified as a hazardous waste under California Law. Other states with different legal and the federal government frameworks do not classify zinc bearing blasting abrasive waste as hazardous waste.